

Guide Information

HSIN HWA CHEMICAL CO LTD

1 YUNG-HSIANG RD, FANG-LIAO HSIANG, PINGTUNG HSIEN 940 TW

HHC000

Methylmethacrylate (MMA), furnished as cast sheets

<u>Color</u>	<u>Min. Thk (mm)</u>	<u>Flame Class</u>	<u>HWI</u>	<u>HAI</u>	<u>RTI Elec</u>	<u>RTI Imp</u>	<u>RTI Str</u>
NC	2.8-3.1	HB	-	-	50	50	50

Comparative Tracking Index (CTI): -	Inclined Plane Tracking (IPT) kV: -
Dielectric Strength (kV/mm): -	Volume Resistivity (10 ^x ohm-cm): -
High-Voltage Arc Tracking Rate (HVTR): -	Surface Resistivity (10 ^x ohms/square): -
Dimensional Stability (%): -	High Volt, Low Current Arc Resis (D495): -

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2020-04-10

Last Revised: 2020-04-12

© 2020 UL LLC



IEC and ISO Test Methods

Test Name	Test Method	Units	Thk (mm)	Value
Flammability	IEC 60695-11-10	Class (color)	2.8-3.1	HB, HB75 (NC)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	°C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	°C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	°C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	°C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m ²	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-1	kJ/m ²	-	-